

Wax Applicator Hose

Wax Connections Inc.

Specifics



- Length of Hose varies between models.
- Handle 5/8" diameter, lever operated by finger
- Adjustable flow via flow control screw
- Fixed heat set @ nominal 185EF
- Quick disconnect from control unit

Features

- Hand held dispenser, like writing with a large pen
- Adjustable flow of seam wax to the pattern
- Continuous flow of wax with the press of a lever
- Interchangeable tips for bead size control
- Fully repairable at our in house location



↷ Wax Applicator Hose (Voltage Regulated) #HT621000

- Lever actuated flow
- Hose length 62"
- Flow control adjusting screw in handle
- Accepts interchangeable tips
- Very flexible feed hose
- *Used on CV211505 control units
(Units are marked with a blue sticker at disconnect, hoses are marked with a blue band by the din plug.)



↷ Wax Applicator Hose (Old Standard) #HL741000

- Lever actuated flow
- Hose length 72"
- Flow control adjusting screw in handle
- Accepts interchangeable tips
- Very flexible feed hose
- *This model used on control units prior to the CV211505 control tanks.



↷ Wax Applicator Hose (Solenoid) #HS741000

- Solenoid actuated flow
- Ideal use for automated processes
- Hose length 72"
- Flow control adjusting screw in handle
- Accepts interchangeable tips
- Very flexible feed hose

When ordering a control unit it is a **good idea** to have a extra hose in storage. In the event the applicator hose that came with your unit needs maintenance. See page (10)